


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:	
PART NO: CB2012-121Y-N				DWG.NO: TE2212100	
CUSTOMER PART NO:				CUST.DWG.NO:	
(1) DIMENSIONS (UNIT: mm) 				A	2.0 ± 0.2 m/m
				B	1.2 ± 0.2 m/m
				C	0.9 ± 0.2 m/m
				D	0.5 ± 0.3 m/m
				E	m/m
				F	m/m
				G	m/m
				H	m/m
				I	m/m
				J	m/m
(2) ELECTRICAL REQUIREMENTS					
Z (Ω)	120 ± 25%	TEST FREQ	100MHz / 100mV		
RDC (Ω)	0.25 (MAX)	TEST FREQ			
IDC (mA)	300 (MAX)	TEST FREQ			
TEST INSTRUMENTS HP4338A MILLIOHMMETER HP4291B FR IMPEDANCE/MATERIAL ANALYZER				APPROVED BY 吳載敏	
				CHECKED BY 張明德	
				DRAWN BY 黃慧診	

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB: www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: CB2012-121Y-N				DWG.NO: TE2212100					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
FREQ	100MHz / 100mV			A	B	C	D		
SPEC	120 $\pm 25\%$	0.25 (MAX)	300 (MAX)	2.0 ± 0.2	1.2 ± 0.2	0.9 ± 0.2	0.5 ± 0.3		
1	108.6	0.026	OK	2.04	1.24	0.90	0.54		
2	116.2	0.025	OK	2.05	1.22	0.90	0.55		
3	114.4	0.027	OK	2.02	1.23	0.91	0.52		
4	115.9	0.025	OK	2.03	1.24	0.91	0.54		
5	114.2	0.027	OK	2.01	1.25	0.89	0.50		
6	116.9	0.025	OK	2.01	1.22	0.89	0.51		
7	116.0	0.026	OK	2.04	1.23	0.90	0.52		
8	115.5	0.027	OK	2.03	1.25	0.92	0.50		
9	112.1	0.026	OK	2.02	1.22	0.89	0.52		
10	124.9	0.026	OK	2.02	1.23	0.88	0.52		
$\bar{X}$	115.5	0.026		2.03	1.23	0.90	0.52		
R	16.3	0.002		0.04	0.03	0.04	0.05		
						APPROVED BY			
						吳載敏			
						CHECKED BY			
						張明德			
						DRAWN BY			
						黃慧診			

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB: www.coremaster.com.tw

CB2012-121Y-N

