


SPECIFICATION FOR APPROVAL

CUSTOMER:				DATE:		
PART NO: LCB1608-600Y-N				DWG.NO: ME9816011		
CUSTOMER PART NO:				CUST.DWG.NO:		
(1) DIMENSIONS (UNIT: mm) 				A	1.6 ± 0.15	m/m
				B	0.8 ± 0.15	m/m
				C	0.8 ± 0.15	m/m
				D	0.2 ~ 0.6	m/m
				E		m/m
				F		m/m
				G		m/m
				H		m/m
				I		m/m
				J		m/m
(2)ELECTRICAL REQUIREMENTS						
Z (Ω)	60 ± 25%	TEST FREQ	100MHz/500mV			
RDC (Ω)	0.04 (MAX)	TEST FREQ				
IDC (mA)	3000 (MAX)	TEST FREQ				
				APPROVED BY 吳載敏		
				CHECKED BY 張明德		
				DRAWN BY Vicky		

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER :				DATE :					
PART NO: LCB1608-600Y-N				DWG.NO: ME9816011					
CUSTOMER PART NO :				CUST.DWG.NO :					
ITEM	Z (Ω)	RDC (Ω)	IDC (mA)	DIMENSION (UNIT : mm)					
FREQ	100MHz /500mV			A	B	C			
SPEC	60 ± 25%	0.04 (MAX)	3000 (MAX)	1.6 ± 0.15	0.8 ± 0.15	0.8 ± 0.15			
1	61.77	0.03	OK	1.56	0.81	0.87			
2	61.22	0.03	OK	1.58	0.81	0.84			
3	62.45	0.03	OK	1.57	0.83	0.84			
4	61.43	0.03	OK	1.58	0.82	0.87			
5	59.88	0.03	OK	1.58	0.85	0.85			
6	60.17	0.03	OK	1.57	0.80	0.83			
7	60.88	0.03	OK	1.57	0.82	0.83			
8	59.66	0.03	OK	1.58	0.82	0.85			
9	61.50	0.03	OK	1.58	0.80	0.83			
10	56.02	0.03	OK	1.55	0.83	0.83			
X	60.50	0.03		1.57	0.82	0.84			
R	6.43	0		0.03	0.05	0.04			
TEST INSTRUMENTS HP-4287A							APPROVED BY 吳載敏		
							CHECKED BY 張明德		
							DRAWN BY Vicky		

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw