



# SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:	
PART NO: RC0810U-221K		DWG.NO: HX4006879	
CUSTOMER PART NO:		CUST.DWG.NO:	
(1) DIMENSION(UNIT: mm)  		A	10.0 (MAX) m/m
		B	12.0 (MAX) m/m
		C	15.0 ± 2.0 m/m
		D	m/m
		E	m/m
		F	m/m
		G	m/m
		H	m/m
		I	m/m
		J	m/m
		(2)ELECTRICAL REQUIREMENTS	
L (uH)	220 ± 10%		
RDC (Ω)	0.6 (MAX)		
IDC (A)	1.5 (MAX)		
TEST CONDITION	1KHz / 0.25V		
		APPROVED BY 吳載敏	
		CHECKED BY 張明德	
		DRAWN BY 黃慧診	

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw

# TEST DATA

CUSTOMER:				DATE:				
PART NO: RC0810U-221K				DWG.NO: HX4006879				
CUSTOMER PART NO :				CUST.DWG.NO :				
TEST CONDITION: 1KHz / 0.25V				DIMENSION (UNIT : mm)				
ITEM	L (uH)	RDC (Ω)	IDC (A)	A	B	C		
SPEC	220 ± 10%	0.6 (MAX)	1.5 (MAX)	10.0 (MAX)	12.0 (MAX)	15.0 ± 2.0		
1	213.4	0.335	OK	9.25	10.66	14.38		
2	213.3	0.337	OK	9.11	10.53	14.33		
3	214.8	0.369	OK	9.06	10.49	14.54		
4	213.2	0.342	OK	9.01	10.50	14.50		
5	213.7	0.333	OK	9.08	10.44	14.30		
6	216.1	0.334	OK	9.23	10.53	14.76		
7	214.4	0.338	OK	9.21	10.57	14.68		
8	213.0	0.353	OK	9.15	10.50	14.77		
9	214.5	0.337	OK	9.05	10.70	14.36		
10	213.2	0.339	OK	9.13	10.54	14.45		
$\bar{X}$	213.96	0.342		9.128	10.546	14.507		
R	3.1	0.036		0.24	0.26	0.47		
TEST INSTRUMENTS HM2791 METER FOR L						APPROVED BY		
						吳載敏		
						CHECKED BY		
						張明德		
						DRAWN BY		
						黃慧診		

**CORE MASTER ENTERPRISE CO., LTD.**

TEL:886-2-8919-1288    FAX:886-2-8919-1298    WEB:www.coremaster.com.tw